

Clarity 5581

Cobalt 309

Specifications

Contents

63% post-consumer recycled polyester
37% antimony-free polyester

Weight

14.6 ± 1.5 oz./lin. yd.

Width

54" min. useable

Repeat

3.75" vertical, 5.4" horizontal

Treatment

Crypton Green stain resistance
Crypton Green odor resistance

Backing

Crypton Green moisture barrier

Treatment

Crypton Green stain resistance
Crypton Green odor resistance

Backing

Crypton Green moisture barrier

Cleaning Code

<p>Standard Care Label W. Clean with water based cleaning agents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.</p>

Performance



Breaking Strength (ASTM D5034)

200 lbf min. warp and 155 lbf min. fill

Tear (ASTM D2261)

25 lbf min. warp and fill

Seam Slippage (ASTM D4034)

105 lbf warp and 85 lbf fill

Pilling resistance (ASTM D3511)

Class 4 min.

Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

Wyzenbeek Abrasion resistance (ASTM D4157)

100,000 double rubs cotton duck

Flammability

CA Technical Bulletin 117-2013 Section 1

Miscellaneous

Every effort has been made to ensure color accuracy of the digital images, however, please order a sample before specification. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Proudly woven in North America supporting our local communities.

