

# Cadence 5595

Citrine 1435

## Specifications

---

### Contents

4% post-consumer recycled polyester  
6% pre-consumer recycled polyester  
90% polyester

### Weight

12.9 ± 1.0 oz./lin. yd.

### Width

54" min. useable

### Repeat

1.5" vertical | 2" horizontal

### Treatment

stain repellent

### Backing

acrylic backcoating

### Treatment

stain repellent

### Backing

acrylic backcoating

## Cleaning Code

---

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

## Performance

---



### Breaking Strength (ASTM D5034)

200 lbf min. warp and 155 lbf min. fill

### Tear (ASTM D2261)

15 lbf min. warp and 25 lbf min. fill

### Seam Slippage (ASTM D4034)

100 lbf warp and 45 lbf fill

### Pilling resistance (ASTM D3511)

Class 4

### Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

### Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

### Wyzenbeek Abrasion resistance (ASTM D4157)

100,000 double rubs cotton duck

### Flammability

CA Technical Bulletin 117-2013 Section 1  
NFPA 260/UFAC Fabric Classification - Class I

## Miscellaneous

---

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended.  
Colors may vary between dye lots. This is a directional fabric.

