To the Point 4732



To the Point 4732

Specifications

Content	56% polyester 44% post-consumer recycled polyester
Weight	8.7 ± 0.5 oz./lin. yd.
Width	54" min. useable
Repeat	none
Backing	SBR backcoating
Treatment	BLOCKaide® stain repellent

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

Performance

Colorfastness to Light (AATCC 16.3 Option 3)
Grade 4 min. at 40 hours

Colorfastness to Crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

×

Breaking Strength (ASTM D5034)

120 lbf min. warp and 150 lbf min. fill

Seam Slippage (ASTM D4034) 30 lbf min. warp and 45 lbf min. fill

Pilling Resistance (ASTM D3511) **Class 4 min.**

Flammability

CA Technical Bulletin 117-2013 Section 1



Abrasion (ASTM D4157) 50,000 double rubs min. cotton duck

Sustainability



tification Marks owned by the Association for Contract Textiles, Inc.

*Not available in USA

