Jane 9085


Blueberry

4091

Natural 4061



Steel 4100



Jet 4040



Gold 4020




Pomegranate



Ultramarine 4030



Persimmon



Chive 4070



Lapis 4041

Jane 9085

Specifications

| Content | 100% pre-consumer recycled polyester |
|-----------|--------------------------------------|
| Weight | 9.7 ± 0.5 oz./lin. yd. |
| Width | 54" min. useable |
| Repeat | none |
| Treatment | BLOCKaide® stain repellent |
| | |

Cleaning Code


Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



| NRC of anechoic termination | 1.00 |
|--|------|
| NRC of fabric in front of anechoic termination | .90 |

Performance

Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours

Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034) 200 lbf min. warp and 130 lbf min. fill

Seam Slippage (ASTM D4034) 50 lbf min. warp and fill

Pilling Resistance (ASTM D3511) Class 4 min.



Flammability

CA Technical Bulletin 117-2013 Section 1 ASTM E84 Class I or A



Abrasion (ASTM D4157) 50,000 double rubs min. cotton duck

Sustainability



100% recycled and recyclable
Terratex is a registered trademark of Duvaltex



(facts[™]

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.



program. Additional testing of this U.L. recognized component fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.