

Frolic 5000

UPHOLSTERY

UPHOLSTERY

Frolic 5000

Specifications

Content	100% polyester
Weight	16.7 ± 1.0 oz./lin. yd.
Width	54" min. useable
Repeat	none
Backing	acrylic backcoating
Treatment	BLOCKaide® stain repellent

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.


Miscellaneous


Proudly woven in North America supporting our local communities.


Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

Performance


-  Colorfastness to Light (AATCC 16.3 Option 3)
Grade 4 min. at 40 hours


-  Colorfastness to Crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

-  Breaking Strength (ASTM D5034)
250 lbf min. warp and fill

- Seam Slippage (ASTM D4034)
50 lbf min. warp and fill

- Pilling Resistance (ASTM D3511)
Class 4 min.

-  Flammability
CA Technical Bulletin 117-2013 Section 1


-  Abrasion (ASTM D4157)
1,000,000 double rubs min. cotton duck

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.


Certification Marks owned by the Association for Contract Textiles, Inc.




Navy
0014




Rust
0032




Red
0002




Mulberry
0012




Aubergine
0072




Cactus
0017




Atlantic
0037




Pine
0007



Blue
0004



Slate
0011



Ink
0006